






MULTI-RANGE TIMER 多段式限時繼電器

SPECIFICATION 規格		H3M-□	H3CT-□
Model 型號			
Dimension(mm) 尺寸		50H*40W*57.5D	48H*48W*84D
Time Range 時間範圍		A: 1S, 10S, 1M, 10M C: 6S, 60S, 6M, 60M E: 3M, 30M, 3H, 30H	B: 3S, 30S, 3M, 30M D: 1M, 10M, 1H, 10H
Supply Voltage 額定電壓		DC(V): 12, 24 AC(V): 12, 24, 48, 110, 220, 240 380, 415, 440, 50/60Hz	
Contact Rating 接點容量		250VAC 5A Resistive Load 48VDC 5A 電阻性負載	
Reset Time 複歸時間		0.2 sec max	
Consumed Power 消耗功率		2VA	
Ambient Temperature 使用周圍溫度		-10°C~+55°C	
Ambient Humidity 使用周圍濕度		45~85%RH	
Life 壽命	Mechanical 機械	5×10 ⁶ times	
	Electrical 電氣	10 ⁵ times	
Weight 重量		160g	170g
Connection 接線圖		<p>限時2C</p>  <p>mode A</p>	<p>限時1C 瞬時1C</p>  <p>mode B</p>
Timing Chart 時序圖		 <p>Rt:Resetting time</p>	 <p>Rt:Resetting time</p>