



## MULTI-RANGE DIGITAL TIMER 多段式數位型限時繼電器

| SPECIFICATION<br>規格           |                  | AH5R-□  | AH6R-□  |
|-------------------------------|------------------|---|---|
| Model<br>型號                   |                  |    |  |
| Dimension(mm)<br>尺寸           |                  | 48H*48W*84D   |   |
| Time Range<br>時間範圍            |                  | x.01Sec, x0.1Sec, x1Sec<br>x0.1Min, 1Min<br>x0.1Hr, x1Hr, x10Hr   |   |
| Features<br>特徵                |                  | <ul style="list-style-type: none"> <li>&gt; Protection against power surge.</li> <li>&gt; 4 timer function selectable: Flicker, Opposite Contact, Count Down, Auto Reset</li> <li>&gt; 防止電源浪湧</li> <li>&gt; 4項可選繼電器功能：閃爍，反接點，倒數，自動複歸</li> </ul> |   |
| Supply Voltage<br>額定電壓        |                  | DC(V): 12, 24<br>AC(V): 12, 24, 48, 110, 220, 240<br>380, 415, 440 50/60Hz  |   |
| Contact Rating<br>接點容量        |                  | 250VAC 5A Resistive Load<br>48VDC 5A 電阻性負載  |   |
| Reset Time<br>複歸時間            |                  | 0.1 sec max   |   |
| Consumed Power<br>消耗功率        |                  | 3VA   |   |
| Ambient Temperature<br>使用周圍溫度 |                  | -10°C ~ +55°C   |   |
| Ambient Humidity<br>使用周圍濕度    |                  | 45~85%RH  |   |
| Life<br>壽命                    | Mechanical<br>機械 | 5×10 <sup>6</sup> times   |   |
|                               | Electrical<br>電氣 | 10 <sup>5</sup> times   |   |
| Weight<br>重量                  |                  | 160g  |   |
| Connection<br>接線圖             |                  | <p>□ -2 限時 1C</p>   | <p>□ -4 限時 1C, 瞬時 1C</p>  |
| Timing Chart<br>時序圖           |                  |   |   |