




DIGITAL TIMER 數位型限時繼電器

SPECIFICATION 規格		H3D-□	H4D-□	H5D-□
Model 型號				
Dimension(mm) 尺寸		48H*48W*84D		
Time Range 時間範圍		Sec : 9.99, 99.9, 999 Min : 99.9, 999, 9M 59S Hr : 99.9, 999, 9H 59M	Sec : 99.99, 999.9, 9999 Min : 999.9, 9999, 99M 59S Hr : 999.9, 9999, 99H 59M	Sec : 999.99, 9999.9, 99999 Min : 9999.9, 99999, 999M 59S Hr : 9999.9, 99999, 999H 59M
Features 特徵		<ul style="list-style-type: none"> > Protection against power surge. > 4 timer function selectable: Flicker, Opposite Contact, Count Down, Auto Reset > 防止電源浪湧 > 4項可選繼電器功能：閃爍，反接點，倒數，自動複歸 		
Supply Voltage 額定電壓		DC(V): 12, 24 AC(V): 12, 24, 48, 110, 220, 240 380, 415, 440 50/60Hz		
Contact Rating 接點容量		250VAC 5A Resistive Load 48VDC 5A 電阻性負載		
Reset Time 複歸時間		0.1 sec max		
Consumed Power 消耗功率		3VA		
Ambient Temperature 使用周圍溫度		-10°C ~ +55°C		
Ambient Humidity 使用周圍濕度		45~85%RH		
Life 壽命	Mechanical 機械	5×10 ⁶ times		
	Electrical 電氣	10 ⁵ times		
Weight 重量		160g		
Connection 接線圖				
Timing Chart 時序圖		