





SPECIAL FUNCTIONS DIGITAL TIMER 特殊功能數位型限時繼電器

SPECIFICATION 規格	H3D-□	H4D-□	H5D-□
Model 型號			
Dimension(mm) 尺寸	48H*48W*84D		
Time Range 時間範圍	Sec : 9.99, 99.9, 999 Min : 99.9, 999, 9M 59S Hr : 99.9, 999, 9H 59M	Sec : 99.99, 999.9, 9999 Min : 999.9, 9999, 99M 59S Hr : 999.9, 9999, 99H 59M	Sec : 999.99, 9999.9, 99999 Min : 9999.9, 99999, 999M 59S Hr : 9999.9, 99999, 999H 59M
Features 特徵	> Protection against power surge. > 4 timer function selectable: Flicker, Opposite Contact, Count Down, Auto Reset > 防止電源浪湧 > 4項可選繼電器功能：閃爍，反接點，倒數，自動複歸		
Supply Voltage 額定電壓	DC(V): 12, 24 AC(V): 12, 24, 48, 110, 220, 240 380, 415, 440 50/60Hz		
Contact Rating 接點容量	250VAC 5A Resistive Load 48VDC 5A 電阻性負載		
Reset Time 複歸時間	0.1 sec max		
Consumed Power 消耗功率	3VA		
Ambient Temperature 使用周圍溫度	-10°C ~ +55°C		
Ambient Humidity 使用周圍濕度	45~85%RH		
Life 壽命	Mechanical 機械	5×10 ⁶ times	
	Electrical 電氣	10 ⁵ times	
Weight 重量	160g		
Connection 接線圖	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>□ -X 限時 1C</p> <p>1+4 Gate 1+3 Reset</p>  </div> <div style="text-align: center;"> <p>□ -P 限時 1C</p> <p>1+4 Gate 1+3 DC12V(NPN Sensor)</p>  </div> </div>		
Timing Chart 時序圖	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  </div> <div style="text-align: center;">  </div> </div>		